



RCstep BP - 40139

Product description

- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Double-sided access.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183

Product features

Base	0,99 m × 0,96 m
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium
Number of treads	4
Number of treads	2 × 4
Overall base width	0.96 m
Platform height	0.99 m



Platform length	300 mm
Platform width	600 mm
Standards	EN 14183
Stile depth	48 mm
Transport dimensions	approx. 1.105 mm × approx. 960 mm × approx. 290 mm
Tread depth	92 mm
Type of rungs/treads	RC tread
Vertical distance between each rung/tread	250 mm
Warranty	10 years
Weight	9.3 kg
Working height	2.99 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 2/7/2026
 Subject to change or error.