




Access steps with landing - 40155466

Stationary access to buildings and machines with platforms.

Product description

- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Stationary access to buildings and machines.
- Individually adjustable platform lengths.
- Support section mounting element for use as a free-standing work platform.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act



(ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

Product features

| | |
|---------------------|-------------------|
| Inclination | 45 ° |
| Load capacity | max. 300 kg |
| Max. load per tread | 150 kg |
| Number of treads | 7 |
| Overall span | 2160 mm |
| Platform length | 600 mm |
| Standards | NF EN ISO 14122-4 |
| Tread width | 1000 mm |
| Vertical height | 1500 mm |
| Warranty | 10 years |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway

CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 27/6/2026

Subject to change or error.