



# Access steps with platform - 40155474

Stationary access to buildings and machines with platforms.

## Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Support section mounting element for use as a free-standing work platform.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Stiles made from high-strength aluminium extrusions with screw channels for flexible assembly options.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



## Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

## Product features



|                                  |                                     |                                      |                                   |                                |
|----------------------------------|-------------------------------------|--------------------------------------|-----------------------------------|--------------------------------|
| Inclination<br><b>45 °</b>       | Load capacity<br><b>max. 300 kg</b> | Max. load per tread<br><b>150 kg</b> | Number of treads<br><b>15</b>     | Overall span<br><b>3881 mm</b> |
| Platform length<br><b>600 mm</b> | Standards<br><b>EN ISO 14122</b>    | Tread width<br><b>1000 mm</b>        | Vertical height<br><b>3220 mm</b> | Warranty<br><b>10 years</b>    |