



## Everest 2E - 4021626

Built for trade and industrial use, the Everest Square-Rung Double Extension Ladder is made in the UK, EN131 certified, and designed for strength, stability, and safety.

### Product description

- Durable, slip-resistant square rungs for secure, comfortable footing.
- Robust, high-performance box-section stiles for maximum strength and stability.
- Secure locking catches keep ladder sections safely locked in position while working or transporting.
- Wrap-around top clips with smooth-glide runners for reduced wear and longer service life.
- Heavy-duty wide stabiliser with slip-resistant feet for maximum safety.



### Hints and special features

Complies with EN 131 Professional.

### Product features

|                              |  |   |  |   |
|------------------------------|--|---|--|---|
| Coating<br><b>natural</b>    | Connection between stiles and rungs/stiles<br><b>flanged</b> | External width of lower ladder<br><b>490 mm</b> | Load capacity<br><b>max. 150 kg</b>        | Material<br><b>aluminium</b>            |
| Number of rungs<br><b>16</b> | Number of rungs<br><b>2 x 16</b>                             | Overall length, extended<br><b>8.33 m</b>       | Overall length, retracted<br><b>4.69 m</b> | Standards<br><b>EN 131 professional</b> |
|                              |  |   |  |   |



**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/everest-2e-4021626>



|   |                             |   |                          |                                 |
|---|-----------------------------|---|--------------------------|---------------------------------|
| Transport dimensions<br><b>approx. 4.690 mm<br/>x approx. 490 mm<br/>x approx. 180 mm</b> | Tread depth<br><b>29 mm</b> | Type of rungs/treads<br><b>serrated</b> | Weight<br><b>26.3 kg</b> | Wide crosspiece<br><b>1.2 m</b> |
| Working height<br><b>8.78 m</b>   |                             |   |                          |                                 |