



Mobile platform steps with ZARGES Ergo Stop - 40255042



Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- An antistatic version of the chassis is also available.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the foot pedal on the flight of steps.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and



guardrails which can be removed without tools.

- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

Product features

Chassis width	Inclination	Load capacity	Max. load per tread	Number of treads
1220 mm	45 °	max. 300 kg	150 kg	12
Overall span	Platform length	Standards	Tread width	Vertical height
3447 mm	600 mm	NF EN ISO 14122-4	800 mm	2790 mm

Warranty
10 years