



# Mobile platform steps with ZARGES Ergo Stop - 40255074



Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

## Product description

- Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- An antistatic version of the chassis is also available.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the foot pedal on the flight of steps.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.



- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

## Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

## Product features

|                     |                   |
|---------------------|-------------------|
| Chassis width       | 1220 mm           |
| Inclination         | 60 °              |
| Load capacity       | max. 300 kg       |
| Max. load per tread | 150 kg            |
| Number of treads    | 5                 |
| Overall span        | 1453 mm           |
| Platform length     | 600 mm            |
| Standards           | NF EN ISO 14122-4 |
| Tread width         | 600 mm            |
| Vertical height     | 1250 mm           |



Warranty

10 years

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 10/5/2026

Subject to change or error.