
DATA SHEET

# Mobile access steps with platform - 40255788

Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.







## PRODUCT DESCRIPTION

- Mobile access or work platforms with easy-going steps. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- An antistatic version of the chassis is also available.
- Narrow chassis: the chassis width is reduced to a minimum through additional ballasting.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

### HINTS AND SPECIAL FEATURES

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.
Standard applied: DIN EN ISO 14 122.

## PRODUCT FEATURES

| Property | Value |
|---|---|
| Chassis width | 1220 mm |
| Inclination | 45 ° |
| Load capacity | max. 300 kg |
| Max. load per tread | 150 kg |
| Number of treads | 9 |
| Overall span | 2558 mm |
| Platform length | 600 mm |
| Standards | NF EN ISO 14122-4 |
| Tread width | 800 mm |
| Vertical height | 1930 mm |
| Warranty | 10 years |

## ACCESSORIES AND SPARE PARTS

**ACCESSORIES** 3



**impact protection**
SKU 41250



**impact protection**
SKU 41252



**impact protection**
SKU 41254

## SPARE PARTS 1

**clamping lever**
SKU 800512

**ZARGES (U.K.) LTD.**
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 31/10/2026
Subject to change or error.