



# Mobile access steps with platform - 40255798

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

## Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



## Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.



Standard applied: DIN EN ISO 14122.

## Product features

Chassis width <b>1420 mm</b>	Inclination <b>45 °</b>	Load capacity <b>max. 300 kg</b>	Max. load per tread <b>150 kg</b>	Number of treads <b>18</b>
Overall span <b>4737 mm</b>	Platform length <b>600 mm</b>	Standards <b>EN ISO 14122</b>	Tread width <b>800 mm</b>	Vertical height <b>4080 mm</b>
Warranty <b>10 years</b>				