



RCstep SP - 40278

Product description

- Platform size approx. 600 x 300 mm
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Extra-deep treads (92 mm) for comfortable and safe standing.
- Single-sided access.
- Safety bar with a practical storage tray.
- Clean hands thanks to wear-resistant anodised stiles.
- New design - high-quality 2-component plastic ladder shoe - also suitable for working on gratings.



Hints and special features

Complies with EN 14 183

Product features

Base	0,82 m × 0,88 m
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	150 kg
Material	Anodised aluminium
Number of rungs, incl. platform	3
Overall base width	0.88 m
Platform height	0.74 m



Platform length	300 mm
Platform width	600 mm
Standards	EN 14183
Stile depth	48 mm
Storage tray	aluminium
Transport dimensions	approx. 1.550 mm × approx. 880 mm × approx. 290 mm
Tread depth	92 mm
Type of rungs/treads	RC tread
Vertical distance between each rung/tread	250 mm
Warranty	10 years
Weight	8.4 kg
Working height	2.74 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 2/7/2026
 Subject to change or error.