



Stationary bridging steps - 40355949

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.





Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

Product features

Clear height, stationary	2030 mm
Inclination	45 °
Load capacity	max. 300 kg
Max. load per tread	150 kg
Number of treads	10
Overall span	5011 mm
Platform length	600 mm
Standards	NF EN ISO 14122-4
Tread width	800 mm
Warranty	10 years

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 31/3/2026
 Subject to change or error.