



ZARGES

More information about the product, accessories and spare parts:  
<https://www.zarges.com/uk/products/stationary-bridging-steps-40355950>



# Stationary bridging steps -

## 40355950

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides.

Large-area platform with guardrail for safe and ergonomic working at heights.



### Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.



### Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act



**ZARGES**

More information about the product, accessories and spare parts:  
<https://www.zarges.com/uk/products/stationary-bridging-steps-40355950>



(ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

## Product features

Clear height, stationary <b>2240 mm</b>	Inclination <b>45 °</b>	Load capacity <b>max. 300 kg</b>	Max. load per tread <b>150 kg</b>	Number of treads <b>11</b>
Overall span <b>5431 mm</b>	Platform length <b>600 mm</b>	Standards <b>NF EN ISO 14122-4</b>	Tread width <b>800 mm</b>	Warranty <b>10 years</b>