



ZARGES

More information about the product, accessories and spare parts:
<https://www.zarges.com/uk/products/stationary-bridging-steps-40355959>



Stationary bridging steps -

40355959

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides.

Large-area platform with guardrail for safe and ergonomic working at heights.



Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Steel gratings (R12) and perforated steel plates (R13) are also available for higher non-slip performance.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Customised guardrail configuration on the platform, with optional swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination: 45° for comfortable access, 60° for confined spaces.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act



ZARGES

More information about the product, accessories and spare parts:
<https://www.zarges.com/uk/products/stationary-bridging-steps-40355959>



(ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14 122.

Product features

Clear height, stationary	Inclination	Load capacity	Max. load per tread	Number of treads
2030 mm	45 °	max. 300 kg	150 kg	10
Overall span	Platform length	Standards	Tread width	Warranty
5011 mm	600 mm	NF EN ISO 14122-4	1000 mm	10 years