



## EFAmix S - 40432

The special ladders for all applications in electrical environments.

### Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base	Connection Stile-Rung	Load capacity	Material	Number of rungs, incl. platform
<b>0,91 m × 0,55 m</b>	<b>flanged</b>	<b>max. 150 kg</b>	<b>Aluminium / plastic</b>	<b>4</b>



Overall base width <b>0.55 m</b>	Overall length <b>1.65 m</b>	Pitch rung/tread <b>230 mm</b>	Platform height <b>0.91 m</b>	Platform length <b>250 mm</b>
Platform width <b>250 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>50 mm</b>	Stile depth <b>50 mm</b>	Stile depth steps/back stay <b>50mm / 50mm</b>
Transport dimensions <b>1.640 mm × approx. 550 mm × 100 mm</b>	Tray <b>Plastic</b>	Tread depth <b>80 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>
Weight <b>7 kg</b>	Working height <b>2.9 m</b>			