



## EFAmix S - 40435

The solution for work in an electrical environment.

### Product description

- The solution for work in an electrical environment.
- Suitable for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Meets the requirements of the high-voltage test for ladders made of insulating material in accordance with DIN EN 61 478.
- Aluminium treads, 80 mm deep, with non-slip ribbing.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in plastic storage tray.
- Only 88 mm wide when folded.
- Treads made of aluminium extrusion.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base	1,4 m × 0,62 m
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Number of rungs, incl. platform	7



Overall base width	0.62 m
Overall length	2.4 m
Platform height	1.6 m
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	50 mm
Stile depth	50 mm
Stile depth steps/back stay	50mm / 50mm
Storage tray	Plastic
Transport dimensions	2.390 mm × approx. 620 mm × 100 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	230 mm
Warranty	10 years
Weight	10 kg
Working height	3.6 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 30/5/2026  
 Subject to change or error.