




## Battery Case - 40582

For the safe storage and transport of defective or damaged lithium batteries in accordance with ADR P908 and SV 376.

### Product description

- Maximum fire protection and easy handling thanks to the fireproof, one-piece interior construction, which also helps to avoid incorrect use.
- Hazardous goods packaging certified for lithium-ion batteries UN 3480, UN 3481.
- Suitable for transporting prototypes, damaged or defective batteries, critically defective batteries and batteries for disposal and recycling.
- Successfully fire-tested: flame does not spread to adjacent batteries, temperature on the container surface remains below 100°C.
- Padding and absorbent material are non-flammable, non-conductive and dust-free.
- Maximum outside temperature below 100°C, no flames or splinters escaping in the event of an accident.
- Capacity per compartment approx. 500 x 150 x 150 mm.
- High-quality special container made of aluminium.
- Equipped with fireproof padding and absorbent material made of textured glass fibres.
- Dust-free interior fittings.
- Tested and approved as hazardous goods packaging in accordance with UN requirements, i.e. can be





transported on public roads.

- For storage and transport of defective or damaged lithium batteries in compliance with ADR special provisions 376 and packing instructions P908.
- New: Meets the specifications laid out by BAM in Special Provision SV 376 for the transport of critically defective lithium batteries.
- Follow the operating instructions.
- Made in Germany

## Hints and special features

Missing translation

## Product features

Colour of the stacking corners <b>Natural aluminium</b>	Corner beading <b>Yes</b>	Fasteners <b>Comfort fasteners</b>	Handles <b>Sprung drop handles</b>	Integrated wheels <b>No</b>
Internal dimensions L x W x H <b>550 mm × 550 mm × 220 mm</b>	Material <b>aluminium</b>	Material of the stacking corners <b>aluminium</b>	Max. gross weight dangerous goods permission <b>65 kg</b>	Number of handles <b>2</b>
Outside dimensions max. L x W x H <b>600 mm × 600 mm × 250 mm</b>	Peripheral beading <b>No</b>	Seal <b>foamed lid seal</b>	Stacking corners <b>Yes</b>	Usable dimensions per compartment <b>500mm × 150mm × 180mm</b>
Volume <b>67 l</b>	Weight <b>11.5 kg</b>			