DATA SHEET

W 172 transport trolley - 40634

Sturdy aluminium trolley for versatile use.



PRODUCT DESCRIPTION

- Sturdy aluminium trolley for a wide variety of applications.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- One of the long sides has a cut-out section measuring approx. 1,230 x 295 mm for convenient loading and unloading.
- Front and side panel reinforcement with all-around and corner beads for high stability.
- One ergonomic handle at either end.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- One long side with cutout section, approx. 1,230 x 295 mm.
- Container cutout with profile-section surround; profile-section joints continuously welded.
- Chassis: 2 swivel and 2 fixed castors, corner-mounted, ∅ 200 mm, 40 mm wide; easy-running, non-marking rubber wheels with roller bearings and thread guards.

PRODUCT FEATURES

Property	Value
Formation Chassis	2 swivel and 2 fixed castors mounted at the corners
Internal dimensions L x W x H	1.500 mm × 900 mm × 700 mm
Material	aluminium

Property	Value
Outside dimensions max. L x W x H	1.650 mm × 950 mm × 980 mm
Peripheral beading	Yes
Volume	945 l
Weight	37 kg
Wheel diameter	200 mm

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 30/10/2026
Subject to change or error.