



## W 172 trolley - 40634

Sturdy aluminium trolley for versatile use.

## **Product description**

- Sturdy aluminium trolley for a wide variety of applications.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- One of the long sides has a cut-out section measuring approx. 1,230 x 295 mm for convenient loading and unloading.
- End and side walls reinforced with peripheral beading and corner beads.
- · One sliding handle at either end.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- One long side with cutout section, approx. 1.230 x 295 mm.
- Side cutout with profile-section surround; profilesection joints continuously welded.
- Chassis: 2 swivel and 2 fixed castors cornermounted, Ø 200 mm, 40 mm wide, easy-running, rubber wheels, "non-marking", roller bearings, thread guards.



## **Product features**

Formation Chassis  2 swivel and 2 fixed castors mounted at the corners	Internal dimensions L x W x H  1.500 mm × 900 mm × 700 mm	Material <b>Aluminium</b>	Outside dimensions max. L x W x H  1.650 mm × 950 mm × 980 mm	Peripheral beading Yes
Volume <b>945 I</b>	Weight 37 kg	Wheel diameter 200 mm		