




## Megastep S - 41146

Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.

### Product description

- Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.
- A sturdy platform that provides a secure footing even during extended periods of work.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- Replaceable two-component plastic end caps that attach securely to the stile and prevent the ladder from slipping.
- Robust design: flanged rung-stile connection with a platform and extruded aluminum profiles.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Base	0,93 m × 0,47 m
Certification	TÜV-SÜD



Coating	anodised
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 250 kg
Material	aluminium
No. of rungs incl. platform	4
Overall base width	0.47 m
Overall length	1.87 m
Platform height	1.06 m
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	73 mm
Stile depth	58 mm
Stile depth steps/back stay	73mm / 58mm
Storage tray	aluminium
Transport dimensions	1.875 mm × 475 mm × 150 mm
Tread depth	60 mm
Type of rungs/treads	SL Step
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	7.3 kg
Working height	3.1 m



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 28/6/2026  
Subject to change or error.