




Megastep S - 41147

Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.

Product description

- Extreme strength meets maximum height: 250 kg load capacity with industry-leading working height for the most demanding applications.
- A sturdy platform that provides a secure footing even during extended periods of work.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable two-component plastic end caps that attach securely to the stile and prevent the ladder from slipping.
- Robust design: flanged rung-stile connection with a platform and extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features



Anti-splay mechanism	Belt strap
Base	1,1 m × 0,5 m
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 250 kg
Material	aluminium
No. of rungs incl. platform	5
Overall base width	0.5 m
Overall length	2.15 m
Platform height	1.33 m
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	73 mm
Stile depth	58 mm
Stile depth steps/back stay	73mm / 58mm
Storage tray	aluminium
Transport dimensions	2.155 mm × 505 mm × 150 mm
Tread depth	60 mm
Type of rungs/treads	SL Step
Vertical distance between each rung/tread	265 mm



Warranty	10 years
Weight	8 kg
Working height	3.35 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway

CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:

sales@zarges.co.uk

www.zarges.com/uk

Effective 28/6/2026

Subject to change or error.