



XLstep S - 41228

Light weight and easy to handle, as well as great value.

Product description


- Light weight and easy to handle, as well as great value.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength Perlon straps prevent splay.
- Triple-riveted connection between rung and stile.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/xlstep-s-41228>

| | | | | |
|---|---------------------------------|---|--|----------------------|
| Anti-splay mechanism | Base | Coating | Connection between stiles and rungs/stiles | Load capacity |
| Belt strap | 1,59 m x 0,63 m | anodised | riveted | max. 150 kg |
| Material | Number of rungs, incl. platform | Overall base width | Overall length | Platform height |
| aluminium | 8 | 0.63 m | 2.91 m | 1.99 m |
| Platform length | Platform width | Standards | Stile depth | Stile depth |
| 250 mm | 300 mm | EN 131 professional | 48 mm | 42 mm |
| Stile depth steps/back stay | Storage tray | Transport dimensions | Tread depth | Type of rungs/treads |
| 48mm / 42mm | aluminium | approx. 2.910 mm x approx. 630 mm x approx. 155 mm | 80 mm | serrated |
| Vertical distance between each rung/tread | Vertical ladder height | Warranty | Weight | Working height |
| 250 mm | 2.67 m | 10 years | 11.7 kg | 4 m |
| certification-mark-pf | | | | |
| TÜV-SÜD | | | | |