



XLstep B - 41264

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- High-strength Perlon straps prevent splay.
- Triple-riveted connection between rung and stile.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism	Belt strap
Base	0,92 m × 0,47 m
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Number of treads	4
Number of treads	2 × 4



Overall base width	0.47 m
Overall length	1.09 m
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	1.090 mm × 470 mm × 170 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Vertical ladder height	0.99 m
Warranty	10 years
Weight	3.4 kg
Working height	2.5 m
certification-mark-pf	TÜV-SÜD

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 31/3/2026
 Subject to change or error.