



## XLstep B - 41265

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

### Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- 80 mm deep surfaces to stand on.
- Wear-resistant, anodised stiles.
- Triple-riveted connection between rung and stile.
- High-strength Perlon straps prevent splay.



### Hints and special features

Complies with EN 131 Professional.



### Product features

Anti-splay mechanism	Belt strap
Base	1,14 m × 0,51 m
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Number of treads	5



Number of treads	2 × 5
Overall base width	0.51 m
Overall length	1.36 m
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	1.360 mm × 500 mm × 170 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Vertical ladder height	1.24 m
Warranty	10 years
Weight	5.8 kg
Working height	2.75 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.  
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 6/4/2026  
 Subject to change or error.