



XLstep B - 41265

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- High-strength Perlon straps prevent splay.
- Triple-riveted connection between rung and stile.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism	Base	Coating	Connection between stiles and rungs/stiles	Load capacity
Belt strap	1,12 m × 0,5 m	anodised	riveted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
aluminium	5	2 × 5	0.5 m	1.36 m
Standards	Stile depth	Transport dimensions	Tread depth	Type of rungs/treads
EN 131 professional	42 mm	1.360 mm × 500 mm × 170 mm	80 mm	serrated
Vertical distance	Vertical ladder height	Warranty	Weight	Working height



ZARGES

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/xlstep-b-41265>



between each rung/
tread

250 mm

1.24 m

10 years

4.5 kg

2.75 m

certification-mark-pf

TÜV-SÜD