



## XLstep B - 41265

Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.

### Product description

- Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.
- Easy access up and down via sturdy 80-mm-deep treads.
- Non-slip two-component ladder feet with a large contact surface.
- Clean hands thanks to wear-resistant anodised stiles.
- Triple-riveted connection between rung and stile.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Durable design for everyday use: extruded aluminum profiles.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti-splay mechanism	Belt strap
Base	1,14 m × 0,51 m
Certification	TÜV-SÜD
Coating	anodised



Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Number of treads	5
Number of treads	2 × 5
Overall base width	0.51 m
Overall length	1.36 m
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	1.360 mm × 500 mm × 170 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Vertical ladder height	1.24 m
Warranty	10 years
Weight	5.8 kg
Working height	2.75 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 1/7/2026  
 Subject to change or error.