



## XLstep B - 41266

Low weight and optimum price/performance ratio  
 without compromising on comfort or equipment.

### Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- High-strength Perlon straps prevent splay.
- Triple-riveted connection between rung and stile.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti-splay mechanism <b>Belt strap</b>	Base <b>1,32 m × 0,53 m</b>	Coating <b>anodised</b>	Connection between stiles and rungs/stiles <b>riveted</b>	Load capacity <b>max. 150 kg</b>
Material <b>aluminium</b>	Number of treads <b>6</b>	Number of treads <b>2 × 6</b>	Overall base width <b>0.53 m</b>	Overall length <b>1.63 m</b>
Standards <b>EN 131 professional</b>	Stile depth <b>42 mm</b>	Transport dimensions <b>1.630 mm × 530 mm × 170 mm</b>	Tread depth <b>80 mm</b>	Type of rungs/treads <b>serrated</b>
Vertical distance	Vertical ladder height	Warranty	Weight	Working height



between each rung/  
tread

**250 mm**

**1.49 m**

**10 years**

**6.1 kg**

**3 m**