



## XLstep B - 41267

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

### Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Stand without fatigue on 80 mm deep treads.
- Wear-resistant, anodised stiles.
- High-strength Perlon straps prevent splay.
- Triple-riveted connection between rung and stile.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti-splay mechanism	Base	Coating	Connection between stiles and rungs/stiles	Load capacity
<b>Belt strap</b>	<b>1,54 m x 0,56 m</b>	<b>anodised</b>	<b>riveted</b>	<b>max. 150 kg</b>
Material	Number of treads	Number of treads	Overall base width	Overall length
<b>aluminium</b>	<b>7</b>	<b>2 x 7</b>	<b>0.56 m</b>	<b>1.9 m</b>
Standards	Stile depth	Transport dimensions	Tread depth	Type of rungs/treads
<b>EN 131 professional</b>	<b>48 mm</b>	<b>1.900 mm x 560 mm x 170 mm</b>	<b>80 mm</b>	<b>serrated</b>
Vertical distance	Vertical ladder height	Warranty	Weight	Working height



**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/xlstep-b-41267>



between each rung/  
tread

**250 mm**

**1.74 m**

**10 years**

**8.3 kg**

**3.25 m**

certification-mark-pf

**TÜV-SÜD**