



XLstep B - 41270

Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.

Product description

- Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.
- Easy access up and down via sturdy 80-mm-deep treads.
- Non-slip two-component ladder feet with a large contact surface.
- Clean hands thanks to wear-resistant anodised stiles.
- Triple-riveted connection between rung and stile.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Durable design for everyday use: extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti-splay mechanism	Belt strap
Base	2,15 m × 0,65 m
Certification	TÜV-SÜD
Coating	anodised



Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Number of treads	10
Number of treads	2 × 10
Overall base width	0.65 m
Overall length	2.71 m
Standards	EN 131 professional
Stile depth	48 mm
Transport dimensions	2.710 mm × approx. 650 mm × 170 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Vertical ladder height	2.49 m
Warranty	10 years
Weight	15.8 kg
Working height	4 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 1/7/2026
 Subject to change or error.