



XLstep B - 41270

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- 80 mm deep surfaces to stand on.
- Wear-resistant, anodised stiles.
- Triple-riveted connection between rung and stile.
- High-strength Perlon straps prevent splay.



Hints and special features

Complies with EN 131 Professional.



Product features

Anti-splay mechanism	Belt strap
Base	2,15 m × 0,65 m
Certification	TÜV-SÜD
Coating	anodised
Connection between stiles and rungs/stiles	riveted
Load capacity	max. 150 kg
Material	aluminium
Number of treads	10



Number of treads	2 × 10
Overall base width	0.65 m
Overall length	2.71 m
Standards	EN 131 professional
Stile depth	48 mm
Transport dimensions	2.710 mm × approx. 650 mm × 170 mm
Tread depth	80 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	250 mm
Vertical ladder height	2.49 m
Warranty	10 years
Weight	15.8 kg
Working height	4 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 2/4/2026
 Subject to change or error.