



# Variomax V - 41383

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

## Product description

- Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.
- Single ladder, stepladder and stair ladder in one.
- Easy-to-use, automatically engaging aluminium safety hinge.
- Safe height adjustment thanks to four pull handles of diecast aluminium.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance EN131-1 (except for the 4x3 model).
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Rung by rung height adjustment in increments of 280 mm.
- Quickly and easily converts from one mode to another.
- High strength, non-twist rung/stile connections.



## Product features

|         |  |                    |                          |                   |
|---------|--|--------------------|--------------------------|-------------------|
| Coating | Connection between stiles and rungs/stiles | Dimensions, folded | Length as lean-to ladder | Length as trestle |
|---------|--|--------------------|--------------------------|-------------------|



ZARGES

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/variomax-v-41383>



|   |  |   |  |                              |
|---|--|---|--|------------------------------|
| <b>natural</b>  | <b>flanged</b>                                 | <b>Missing translation</b>                    | <b>4.2 m</b>   | <b>2 m</b>                   |
| Load capacity<br><b>max. 150 kg</b>                               | Material<br><b>aluminium</b>                   | Number of rungs<br><b>4</b>                   | Number of rungs<br><b>4 x 4</b>                            | Standards<br><b>EN 131-4</b> |
| Transport dimensions<br><b>1.310 mm x approx. 640 mm x 210 mm</b> | Tread depth<br><b>30 mm</b>                    | Type of rungs/treads<br><b>serrated</b>       | Vertical distance between each rung/tread<br><b>265 mm</b> | Warranty<br><b>10 years</b>  |
| Weight<br><b>15 kg</b>  | Working height as lean-to ladder<br><b>5 m</b> | Working height as stepladder<br><b>3.35 m</b> | certification-mark-pf<br><b>TÜV-SÜD</b>                    |                              |