



## Variomax V - 41384

Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.

### Product description

- Multifunctional, extendible ladder suitable for use on stairs, with compact transport dimensions and in sturdy, durable design.
- Single ladder, stepladder and stair ladder in one.
- Easy-to-use, automatically engaging aluminium safety hinge.
- Safe height adjustment thanks to four pull handles of diecast aluminium.
- Fitted with fold-out stabilisers to allow the product to be used as a single ladder in compliance EN131-1 (except for the 4x3 model).
- The stabilisers can be folded in to save space during transport or when the product is used as a stepladder.
- Rung by rung height adjustment in increments of 280 mm.
- Quickly and easily converts from one mode to another.
- High strength, non-twist rung/stile connections.



### Product features

|               |         |
|---------------|---------|
| Certification | TÜV-SÜD |
| Coating       | natural |



|  |                                    |
|--|------------------------------------|
| Connection between stiles and rungs/stiles | flanged                            |
| Dimensions, folded                         | Missing translation                |
| Length as lean-to ladder                   | 5.3 m                              |
| Length as trestle                          | 2.54 m                             |
| Load capacity                              | max. 150 kg                        |
| Material                                   | aluminium                          |
| Number of rungs                            | 5                                  |
| Number of rungs                            | 4 × 5                              |
| Standards                                  | EN 131-4                           |
| Transport dimensions                       | 1.580 mm × approx. 710 mm × 210 mm |
| Tread depth                                | 30 mm                              |
| Type of rungs/treads                       | serrated                           |
| Vertical distance between each rung/tread  | 265 mm                             |
| Warranty                                   | 10 years                           |
| Weight                                     | 18 kg                              |
| Working height as lean-to ladder           | 6.05 m                             |
| Working height as stepladder               | 3.85 m                             |

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.

Bletchley MK1 1QU

Tel: 01908 641118

Fax:

[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 16/5/2026

Subject to change or error.