



# Skymaster X - 41537

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Ladder length as 3-part single ladder <b>5 m</b>	Length as 2-part single ladder and as stepladder with push- on section	Load capacity <b>max. 150 kg</b>
---------------------------	---	--	---	-------------------------------------



			<b>3.6 m</b>	
<b>Material</b> <b>aluminium</b>	<b>Number of rungs</b> <b>7</b>	<b>Number of rungs</b> <b>3 × 7</b>	<b>Overall length, retracted</b> <b>2.2 m</b>	<b>Rigid locking bar</b> <b>on one side</b>
<b>Standards</b> <b>EN 131</b> <b>professional</b>	<b>Stile depth</b> <b>68 mm</b>	<b>Transport dimensions</b> <b>2.160 mm × 500 mm × 180 mm</b>	<b>Tread depth</b> <b>30 mm</b>	<b>Type of rungs/treads</b> <b>serrated</b>
<b>Vertical distance between each rung/tread</b> <b>265 mm</b>	<b>Warranty</b> <b>10 years</b>	<b>Weight</b> <b>15 kg</b>	<b>Wide crosspiece</b> <b>0.9 m</b>	<b>Working height as 3-part single ladder</b> <b>5.8 m</b>

certification-mark-pf

**TÜV-SÜD**