



Skymaster X - 41537

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection between stiles and rungs/stiles flanged	Ladder length as 3-part single ladder 5 m	Length as 2-part single ladder and as stepladder with push-on section	Load capacity max. 150 kg
---------------------------	--	---	---	-------------------------------------



			3.6 m	
Material aluminium	Number of rungs 7	Number of rungs 3 × 7	Overall length, retracted 2.2 m	Rigid locking bar on one side
Standards EN 131 professional	Stile depth 68 mm	Transport dimensions 2.160 mm × 500 mm × 180 mm	Tread depth 30 mm	Type of rungs/treads serrated
Vertical distance between each rung/ tread 265 mm	Warranty 10 years	Weight 15 kg	Wide crosspiece 0.9 m	Working height as 3- part single ladder 5.8 m