



Skymaster X - 41538

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Can be used on steps/stairs.
- Upper ladder can also be used separately as single ladders.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/skymaster-x-41538>

Coating natural	Connection between stiles and rungs/stiles flanged	Ladder length as 3-part single ladder 5.8 m	Length as 2-part single ladder and as stepladder with push- on section 4.1 m	Load capacity max. 150 kg
Material aluminium	Number of rungs 8	Number of rungs 3 × 8	Overall length, retracted 2.45 m	Rigid locking bar on one side
Standards EN 131 professional	Stile depth 73 mm	Transport dimensions 2.440 mm × 500 mm × 200 mm	Tread depth 30 mm	Type of rungs/treads serrated
Vertical distance between each rung/ tread 265 mm	Warranty 10 years	Weight 17.5 kg	Wide crosspiece 1 m	Working height as 3- part single ladder 6.65 m
certification-mark-pf				
TÜV-SÜD				