



Skymaster X - 41539

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged



Ladder length as 3-part single ladder	6.7 m
Length as 2-part single ladder and as stepladder with push-on section	4.7 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	9
Number of rungs	3 × 9
Overall length, retracted	2.7 m
Rigid locking bar	on one side
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	2.730 mm × 500 mm × 200 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	20 kg
Wide crosspiece	1.1 m
Working height as 3-part single ladder	7.45 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 10/6/2026
 Subject to change or error.