



# Skymaster X - 41540

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Can be used on steps/stairs.
- Upper ladder can also be used separately as single ladders.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
---------------	---------



Coating	natural
Connection between stiles and rungs/stiles	flanged
Ladder length as 3-part single ladder	6.9 m
Length as 2-part single ladder and as stepladder with push-on section	4.95 m
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	10
Number of rungs	3 × 10
Overall length, retracted	3 m
Rigid locking bar	on one side
Standards	EN 131 professional
Stile depth	85 mm
Transport dimensions	3.010 mm × 500 mm × 210 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	265 mm
Warranty	10 years
Weight	25.2 kg
Wide crosspiece	1.1 m
Working height as 3-part single ladder	7.7 m



ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway  
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:  
[sales@zarges.co.uk](mailto:sales@zarges.co.uk)

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 10/6/2026  
Subject to change or error.