



# Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Cannot be used on stairs.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating	Connection between stiles and rungs/stiles	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	--	---------------------------------------	---	---------------



**ZARGES**

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/skymaster-x-41542>



<b>natural</b>	<b>flanged</b>	<b>8.6 m</b>	on section <b>6.1 m</b>	<b>max. 150 kg</b>
Material <b>aluminium</b>	Number of rungs <b>12</b>	Number of rungs <b>3 × 12</b>	Overall length, retracted <b>3.55 m</b>	Rigid locking bar <b>on one side</b>
Standards <b>EN 131 professional</b>	Stile depth <b>98 mm</b>	Transport dimensions <b>3.590 mm × 500 mm × 230 mm</b>	Tread depth <b>30 mm</b>	Type of rungs/treads <b>serrated</b>
Vertical distance between each rung/ tread <b>265 mm</b>	Warranty <b>10 years</b>	Weight <b>30.1 kg</b>	Wide crosspiece <b>1.2 m</b>	Working height as 3- part single ladder <b>9.35 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				