



Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Cannot be used on stairs.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection between stiles and rungs/stiles	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	--	---------------------------------------	---	---------------



natural	flanged	8.6 m	on section 6.1 m	max. 150 kg
Material aluminium	Number of rungs 12	Number of rungs 3 × 12	Overall length, retracted 3.55 m	Rigid locking bar on one side
Standards EN 131 professional	Stile depth 98 mm	Transport dimensions 3.590 mm × 500 mm × 230 mm	Tread depth 30 mm	Type of rungs/treads serrated
Vertical distance between each rung/ tread 265 mm	Warranty 10 years	Weight 30.1 kg	Wide crosspiece 1.2 m	Working height as 3- part single ladder 9.35 m