



Skymaster X - 41544

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Cannot be used on stairs.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection between stiles and rungs/stiles	Ladder length as 3-part single ladder	Length as 2-part single ladder and as stepladder with push-	Load capacity
---------	--	---------------------------------------	---	---------------



ZARGES

More information about the product, accessories and spare parts:

<https://www.zarges.com/uk/products/skymaster-x-41544>



natural	flanged	9.7 m	on section 6.95 m	max. 150 kg
Material	Number of rungs	Number of rungs	Overall length, retracted	Rigid locking bar
aluminium	14	3 × 14	4.15 m	on one side
Standards	Stile depth	Transport dimensions	Tread depth	Type of rungs/treads
EN 131 professional	98 mm	4.140 mm × 500 mm × 230 mm	30 mm	serrated
Vertical distance between each rung/ tread	Warranty	Weight	Wide crosspiece	Working height as 3- part single ladder
265 mm	10 years	37.9 kg	1.2 m	10.4 m
certification-mark-pf				
TÜV-SÜD				