



Skymaster X - 41544

Convertible to take on challenging tasks with greater safety.

Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- Cannot be used on stairs.
- Anti-spread protection provided by high-strength polyester webbing with a sewn-in attachment tab.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|---------------|---------|
| Certification | TÜV-SÜD |
| Coating | natural |



| | |
|---|----------------------------|
| Connection between stiles and rungs/stiles | flanged |
| Ladder length as 3-part single ladder | 9.7 m |
| Length as 2-part single ladder and as stepladder with push-on section | 6.95 m |
| Load capacity | max. 150 kg |
| Material | aluminium |
| Number of rungs | 14 |
| Number of rungs | 3 × 14 |
| Overall length, retracted | 4.15 m |
| Rigid locking bar | on one side |
| Standards | EN 131 professional |
| Stile depth | 98 mm |
| Transport dimensions | 4.140 mm × 500 mm × 230 mm |
| Tread depth | 30 mm |
| Type of rungs/treads | serrated |
| Vertical distance between each rung/tread | 265 mm |
| Warranty | 10 years |
| Weight | 37.9 kg |
| Wide crosspiece | 1.2 m |
| Working height as 3-part single ladder | 10.4 m |

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 14/5/2026
 Subject to change or error.