



## Alto L - 41550

The compact alternative - with respect to size, weight and price/performance ratio.

### Product description

- The compact alternative - with respect to size, weight and price/performance ratio.
- Very lightweight but extremely stable.
- Rung depth 30 mm.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	10
Overall length	3.05 m
Standards	EN 131 professional



Stile depth	58 mm
Transport dimensions	3.050 mm × 350 mm × 60 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	270 mm
Warranty	10 years
Weight	6.1 kg
Wide crosspiece	0.79 m
Working height	3.9 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue, Saxon Park Ind. Est.  
Bletchley MK1 1QU

Tel: 01908 641118

Fax:  
sales@zarges.co.uk

[www.zarges.com/uk](http://www.zarges.com/uk)

Effective 2/4/2026  
Subject to change or error.