



## Alto L - 41552

The compact alternative - with respect to size, weight and price/performance ratio.

### Product description

- The compact alternative - with respect to size, weight and price/performance ratio.
- Very lightweight but extremely stable.
- Rung depth 30 mm.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>aluminium</b>	Number of rungs <b>12</b>
Overall length <b>3.61 m</b>	Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>3.610 mm × 350 mm × 60 mm</b>	Tread depth <b>30 mm</b>
Type of rungs/treads <b>serrated</b>	Vertical distance between each rung/tread <b>270 mm</b>	Warranty <b>10 years</b>	Weight <b>7 kg</b>	Wide crosspiece <b>0.79 m</b>



Working height

**4.4 m**

certification-mark-pf

**TÜV-SÜD**