



Alto L - 41564

The compact alternative—in terms of both size and weight, as well as price/performance.

Product description

- The compact alternative—in terms of both size and weight, as well as price/performance.
- Very lightweight but extremely stable.
- Rung depth 30 mm.
- Outside width: 350 mm.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from aluminium extrusions.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection between stiles and rungs/stiles	flanged
Load capacity	max. 150 kg
Material	aluminium
Number of rungs	24
Overall length	6.98 m
Standards	EN 131 professional



Stile depth	85 mm
Transport dimensions	6.970 mm × 350 mm × 90 mm
Tread depth	30 mm
Type of rungs/treads	serrated
Vertical distance between each rung/tread	270 mm
Warranty	10 years
Weight	14.4 kg
Wide crosspiece	1.1 m
Working height	7.7 m

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 1/6/2026
Subject to change or error.