



ZAP Safemaster S - 41672

The flanged platform ladder can now be retrofitted with triangular stabilisers to comply with EN 131-7.

Product description

- The flanged platform ladder can now be retrofitted with triangular stabilisers to comply with EN 131-7.
- Optimal stability thanks to a rigid connection on both sides with pressure reinforcement.
- Foldable anodised handrails allow it to take up less space during transport.
- The handle on the platform allows the ladder to be folded up quickly and effortlessly.
- Aluminum work platform, approx. 400 x 400 mm, with three-sided safety railing (height 1,000 mm).
- Anodised handrails and guardrails.
- Generously sized storage tray for tools and small parts.
- 80 mm deep treads with ZARGES Safer Step Technology.
- Can be retrofitted with optional stabiliser sets to comply with EN 131, Part 7.



Product features

| | |
|--------------------------|-------------------|
| Anti-splay mechanism | Rigid locking bar |
| Certification | TÜV-SÜD |
| Guardrail height | 1000 mm |
| Height including railing | 1.53 m |



| | |
|---------------------------------|------------------------------------|
| Load capacity | max. 150 kg |
| Number of rungs, incl. platform | 2 |
| Overall base width | 0.59 m |
| Overall length | 1.87 m |
| Platform height | 0.53 m |
| Platform length | 400 mm |
| Platform material | Aluminium ribbed plate |
| Platform width | 400 mm |
| Standards | EN 131 professional |
| Stile depth | 73 mm |
| Stile depth | 58 mm |
| Stile depth steps/back stay | 73mm / 58mm |
| Storage tray | aluminium |
| Transport dimensions | approx. 1.870 mm × 620 mm × 210 mm |
| Tread depth | 80 mm |
| Type of rungs/treads | Safer Step |
| Warranty | 10 years |
| Weight | 10.6 kg |
| Working height | 2.53 m |

ZARGES (U.K.) Ltd.

Blackwater Trading Estate, The Causeway
 CM9 4LJ Maldon, Essex

Tel: 01908 641118

Fax:
sales@zarges.co.uk

www.zarges.com/uk

Effective 28/6/2026
 Subject to change or error.