



ZAP Safemaster S - 41677

Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.

Product description

- Safe ascent and descent due to non-slip treads and handrail, high degree of stability and compact transport dimensions.
- Optimum stability thanks to rigid locking bar on both sides.
- Foldable anodised handrails allow it to take up less space during transport.
- The handle on the platform allows the ladder to be folded up quickly and effortlessly.
- Extra-large work platform (400 x 400 mm).
- Anodised handrails and guardrails.
- Generously sized storage tray for tools and small parts.
- Treads 80 mm deep, with ZARGES Safer Step Technology.
- Can be retrofitted with optional stabiliser sets to comply with EN 131, Part 7.



Product features

| | | | | |
|----------------------------------------|------------------------------------|-------------------------------------------|-------------------------------------|----------------------------------------------------|
| Anti splay Rigid locking bar | Guardrail height 1000 mm | Height including railing 2.87 m | Load capacity max. 150 kg | Number of rungs, incl. platform 7 |
| Overall base width 0.74 m | Overall length 3.27 m | Platform height 1.85 m | Platform length 400 mm | Platform material Aluminium ribbed plate |
| | | | | |



| | | | | |
|-------------------------------------------------------------------|-----------------------------------------|-----------------------------|--------------------------------------|---------------------------------------------------|
| Platform width 400 mm | Standards EN 131 professional | Stile depth 73 mm | Stile depth 58 mm | Stile depth steps/back stay 73mm / 58mm |
| Transport dimensions approx. 3.270 mm x 720 mm x 210 mm | Tray Aluminium | Tread depth 80 mm | Type rung/tread Safer Step | Warranty 10 years |
| Weight 17.4 kg | Working height 3.85 m | | | |