



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41952

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



Product features

Base	0,82 m × 1,45 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Guardrail height	1000 mm
Load capacity	max. 150 kg
Material	Aluminum/steel, galvanised
Number of rungs, incl. platform	4
Platform height	0.96 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.350 mm × 830 mm × 410 mm
Tread depth	200 mm
Type of rungs/treads	Open-grid surface
Vertical distance between each rung/tread	240 mm
Warranty	10 years
Weight	47.5 kg
Working height	2.95 m

ZARGES (U.K.) Ltd.

8 Holdom Avenue. Saxon Park Ind. Est.
 Bletchley MK1 1QU

Tel: 01908 641118

Fax:
 sales@zarges.co.uk

www.zarges.com/uk

Effective 20/4/2026
 Subject to change or error.