



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41954

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.



Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through platform guardrail at a height of 1.00 m on three sides.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



Product features

Base 0,93 m × 1,81 m	Coating natural	Connection between stiles and rungs/stiles welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material Aluminum/steel, galvanised	Number of rungs, incl. platform 6	Platform height 1.44 m	Platform length 800 mm	Platform width 600 mm
Standards EN 131-7	Transport dimensions 1.820 mm × 930 mm × 350 mm	Tread depth 200 mm	Type of rungs/treads Open-grid surface	Vertical distance between each rung/tread 240 mm
Warranty 10 years	Weight 59.7 kg	Working height 3.45 m		