



# Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41954

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

## Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

## Product features

Base <b>0,93 m × 1,81 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>welded</b>	Guardrail height <b>1000 mm</b>	Load capacity <b>max. 150 kg</b>
Material	Number of rungs, incl.	Pitch rung/tread	Platform height	Platform length



<b>Aluminum/steel, galvanised</b>	platform <b>6</b>	<b>240 mm</b>	<b>1.44 m</b>	<b>800 mm</b>
Platform width <b>600 mm</b>	Standards <b>EN 131-7</b>	Transport dimensions <b>1.820 mm × 930 mm × 350 mm</b>	Tread depth <b>200 mm</b>	Type rung/tread <b>Open-grid surface</b>
Warranty <b>10 years</b>	Weight <b>59.7 kg</b>	Working height <b>3.45 m</b>		