



Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41956

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

Product features

Base 1,03 m × 2,17 m	Coating natural	Connection Stile-Rung welded	Guardrail height 1000 mm	Load capacity max. 150 kg
Material	Number of rungs, incl.	Pitch rung/tread	Platform height	Platform length



Aluminum/steel, galvanised	platform 8	240 mm	1.92 m	800 mm
Platform width 600 mm	Standards EN 131-7	Transport dimensions 2.220 mm × 1.130 mm × 350 mm	Tread depth 200 mm	Type rung/tread Open-grid surface
Warranty 10 years	Weight 72.9 kg	Working height 3.9 m		