DATA SHEET

Mobile access steps with platform, double-sided access, with steel open-grid treads and platform -

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.



PRODUCT DESCRIPTION

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.





HINTS AND SPECIAL FEATURES

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.
Complies with EN 131-7

PRODUCT FEATURES

Property	Value
Base	0,82 m × 1,79 m
Coating	natural
Connection between stiles and rungs/stiles	welded
Guardrail height	1000 mm

Property	Value
Load capacity	max. 150 kg
Material	Aluminum / Steel, galvanised
Number of rungs, incl. platform	2 × 4
Number of treads	4
Platform height	0.96 m
Platform length	800 mm
Platform width	600 mm
Standards	EN 131-7
Transport dimensions	1.960 mm × 830 mm × 300 mm
Tread depth	200 mm
Type of rungs/treads	Open-grid surface
Vertical distance between each rung/tread	240 mm
Warranty	10 years
Weight	59.2 kg
Working height	2.95 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 2



Pole barrier
SKU 41957



Storage tray
SKU 41967

SPARE PARTS 6



Castor, antistatic
SKU 803298



Push-on end cap
SKU 824409



Push-on end cap, antistatic
SKU 824475



Sprung castor for platform steps
SKU 802198



Sprung castor for platform steps
SKU 802199



User instructions label
SKU 800597

ZARGES (U.K.) LTD.
Blackwater Trading Estate,
The Causeway
CM9 4LJ Maldon, Essex

Tel: 01908 641118
sales@zarges.co.uk

www.zarges.com/uk
Effective 31/10/2026
Subject to change or error.