



# Mobile access steps with platform, double-sided access, with steel open-grid treads and platform - 41964

The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.



## Product description

- The flexible solution for wet-room applications, with open-grid treads for improved non-slip performance.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and quick to set up with four sprung swivel castors (two of which have brakes).
- Maximum safety through double-sided platform guardrail at a height of 1.00 m.
- Comfortable ascent thanks to 200 mm deep treads.
- Large platform, 600 x 800 mm.
- Maximum load 150 kg.

## Hints and special features

Optional double-sided handrail in compliance with DIN EN 131-7 on the steps.

Complies with EN 131-7



## Product features

Base <b>0,93 m × 2,34 m</b>	Coating <b>natural</b>	Connection between stiles and rungs/stiles <b>welded</b>	Guardrail height <b>1000 mm</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminum/steel, galvanised</b>	Number of rungs, incl. platform <b>2 × 6</b>	Number of treads <b>6</b>	Platform height <b>1.44 m</b>	Platform length <b>800 mm</b>
Platform width <b>600 mm</b>	Standards <b>EN 131-7</b>	Transport dimensions <b>2.140 mm × 930 mm × 380 mm</b>	Tread depth <b>200 mm</b>	Type of rungs/treads <b>Open-grid surface</b>
Vertical distance between each rung/tread <b>240 mm</b>	Warranty <b>10 years</b>	Weight <b>80.7 kg</b>	Working height <b>3.45 m</b>	